

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/084451 A1

(51) International Patent Classification⁷: **A23C 3/037**,
A23L 3/18, B01D 5/00

(74) Agent: **BRUNNSTRÖM, Gunilla**; AB Tetra Pak, Patent
Department, Ruben Rausing's gata, S-221 86 Lund (SE).

(21) International Application Number:
PCT/SE2005/000324

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 3 March 2005 (03.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0400520-3 3 March 2004 (03.03.2004) SE

(71) Applicant (for all designated States except US): **TETRA
LAVAL HOLDINGS & FINANCE SA** [CH/CH]; Avenue
Général-Guisan 70, CH-1009 Pully (CH).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **RINGSTRÖM,
Roland** [SE/SE]; Päröngatan 2, S-240 14 Veberöd (SE).

[Continued on next page]

(54) Title: AN APPARATUS FOR THE EVAPORATIVE COOLING OF A LIQUID PRODUCT



(57) Abstract: The disclosure relates to an apparatus for the evaporative cooling of a liquid product. The apparatus comprises a vacuum chamber (1) which is divided into a first, centrally positioned space (6) and a second space (7) which concentrically surrounds the first space (6). Both of the spaces (6, 7) are open towards the upper end wall (2) of the vacuum chamber (1). The first space (6) has an outlet (25) for condensed steam. The second space (7) has an inlet (11) for steamed product, as well as an outlet (12) for the product. The apparatus also includes a circulation circuit for coolant liquid. The first space (6) is extended downwards so that it extends at least as far below the bottom end wall (4) of the vacuum chamber (1) as the extent of the space (6) inside the vacuum chamber (1).



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*